

From Forest Nursery Notes, Summer 2011

74. Pipe insulation is an inexpensive, energy-saving measure. Bartok, J. W., Jr.
Greenhouse Management and Production 30(10):58-59. 2010.



By John W. Bartok Jr.

Pipe insulation is an inexpensive, energy-saving measure

In conducting energy audits of greenhouse operations, I've frequently observed uninsulated hot-water system piping.

These are in areas where heat is not needed or where better heat control could be obtained if piping was insulated. It's surprising how much heat an uninsulated pipe gives off.

I know one grower with two large boilers heating a gutter-connected greenhouse. He told me that before insulating the supply/return pipes in his boiler room, he frequently had to leave the windows and doors open or it would get too hot in the room to work. Once the pipes were insulated, extra heat had to be added to the room to make it comfortable.

Heat loss from pipes depends on several factors, including the diameter and length of the pipe, the water temperature inside the pipe, the air temperature surrounding the pipe and the length of time the pipe is carrying hot water. Adding insulation slows the heat loss and lowers the fuel bill.

Estimating your savings

Table 1 provides the approximate annual savings from insulating a linear foot of different diameter pipe with 1-inch of fiberglass or foam. It assumes 2,000 hours of annual use, typical of a greenhouse heating system in a

northern climate.

To use the table, select a pipe diameter and multiply the length of pipe by the savings given in the table. For example, a grower can save \$372 a year by insulating 100 feet of 2-inch diameter heating system pipe carrying 180°F water if the boiler is fired with natural gas costing \$1.05 per therm. The savings from the pipe insulation = 100 feet × \$3.72 per linear foot = \$372.

Selecting an insulation material

Pipe-insulating materials are selected based on where the heating pipes are located, maximum temperature of the water and the insulating value of the insulation material. Most insulation materials are available with formed pieces to fit over pipe elbows and tees.

All insulation materials are flexible or semi-rigid except for those that are enclosed in a protective jacket. This makes them easy to install in tight locations. Depending on the material, the length of individual pieces may be 2 to 6 feet long. These pieces can be cut with a utility knife to the desired length. All materials can either be slit to fit over an existing pipe or come in two pieces.

Due to the low service temperature, polyethylene materials are fine for use in domes-

Table 1. Approximate annual fuel savings with pipe insulation (per linear foot)*

Nominal diameter (inches)	Surface area (sq. ft.)	Heat loss bare pipe (Btu/hour-foot)	Heat loss 1" insulation (Btu/hour-foot)	Natural gas @ \$1.05/therm	Fuel oil @ \$2/gallon	Propane @ \$1.75/gallon
½	0.22	52	11.5	\$1.22	\$1.62	\$2.43
¾	1.05	65	13	\$1.56	\$2.08	\$3.12
1	1.32	82	15	\$2.01	\$2.68	\$4.02
1¼	1.66	102	18	\$2.52	\$3.36	\$5.04
1½	1.9	118	19	\$2.97	\$3.96	\$5.94
2	2.4	147	23	\$3.72	\$4.96	\$7.44
3	3.5	218	30	\$5.64	\$7.52	\$11.28
4	4.5	279	37	\$7.26	\$9.68	\$14.52
6	6.6	409	51	\$10.74	\$14.32	\$21.48

* Steel pipe, 180°F water temperature, 70°F room air temperature, 2,000 hours per year, 1-inch foam insulation, 70 percent heating system efficiency

tic hot water systems, but should not be used where the boiler water is greater than 200°F. All other materials can withstand higher temperatures.

Table 2 gives the insulation factor for the different materials. The lower the "k" value, the better the insulation value of the material and the greater the savings. Except for domestic hot-water pipes that may contain 140°F water, all piping should be covered with at least 1-inch thick insulation.

Insulation installation

The time it takes to install pipe insulation depends on the material and access to put it on. Average time varies between 250 feet per day for smaller size pipe to 80 feet per day for larger size pipe.

Scaffolding or a man-lift may be required for installation in some greenhouses. If a heating contractor installs the insulation, expect to pay labor costs of about \$2.50 per linear foot for small

Table 2. Pipe insulation selection.

Insulation material	Maximum pipe temperature	Insulation factor k*	Cost	Application
Polyethylene	180°F	0.29	Very low	Indoor/outdoor
UV polyethylene	200°F	0.25	Very low	Outdoor/underground
Elastomer foam rubber	220°F	0.27	Low	Indoor
Urethane foam	300°F	0.19	Medium	Indoor
Cellular glass	400°F	0.29	Medium	Outdoor/underground
Fiberglass	850°F	0.23	Medium	Indoor/jacket
Rock fiber	1,200°F	0.24	High	Indoor

*k is conductivity in Btu-inch/hour-square foot-°F at 75°F

size pipe to about \$4 for larger pipe. If the insulation installation is done with the greenhouse labor force during slower periods, it may cost considerably less.

Payback for most pipe installation will be less than two years. USDA or state grant money may be available to offset

some of the cost. Visit www.dsireusa.org for information on grant programs.

John Bartok Jr. is faculty emeritus, University of Connecticut, Department of Natural Resources Management and Engineering, jbartok@rcn.com.

Solar Solutions

Solar Panel Kits include:

Solar Panel(s), Solar Charge Controller, 12 to 24 V converter, staged curtain controller & 5 day back-up with AGM sealed battery(s) in an enclosure.



Solar Panel Kit - (complete)

1 to 5

Same as above w/ added solar wattage & battery storage provided for 1 inflation fan. Includes relays for Roll-Lock application. \$2380.00

Same as above with additional relays for our Roll-Lock application. \$2580.00

Same as line 1 with added solar wattage and battery storage provided for 1 inflation fan. \$3180.00

Same as line 1 with added solar wattage and battery storage provided for 1 inflation fan. Includes relays for Roll-Lock. \$3380.00

Our Low Voltage Motors provide great curtain rolling power in Greenhouses.

60 NM One direction output, 24V, 2A, 4.5 RPM, 28 Rev 1 to 5

LVM w/wheel set, guidepipe hardware & adapter for 1.3" roll-bar \$449.80

Low Voltage Motor above for 1.6" roll-bar \$459.80

Low Voltage Motor above for 2.3" roll-bar \$469.80

Low Voltage Motor above for Side-Clasp roll-bar \$469.80

Low Voltage Motor ONLY - 60 NM \$390.00



Fully Automated SOLAR POWERED Natural Ventilation

Controllers:

1 to 5

Solar Panel Control for 2 LVMs, with Curtain Controller, Converter, Solar Charge Controller Panel mounted on curtain. \$1590.00

Solar Panel Control for 2 LVMs, with Curtain Controller, Converter, Solar Charge Controller when using Roll-Lock. \$1790.00

12V Control, for customers with existing 12V input source for 2 Low Voltage Motors. Has a 24V Converter. \$ 948.00

12V Control, for customers with existing 12V input source. Has a 24V Converter. For 2 LVMs using Roll-Lock. \$1180.00

ADVANCING ALTERNATIVESSM

717 Schuylkill Mountain Road
Schuylkill Haven, PA 17972
Ph: 570-739-1034 * Fax: 570-739-1258
TOLL FREE: 877-546-2257

www.advancingalternatives.com

Greenhouse[®]

MANAGEMENT & PRODUCTION

DEPARTMENTS

- 4 Outlook
David Kuack
- 6 Culture
Heucherella
- 60 People & Events
- 63 Marketplace
- 64 Classifieds
- 66 Ad Index

COLUMNS

- 58 Technology
John W. Bartok Jr.

SPECIAL INSERT:



2011 Profit Quest Supplement

See what growers are doing to boost their bottom lines.

ON THE COVER

Jerry Soukup of Southwest Perennials in Dallas, grows a variety of herb and perennial plugs, including drought-tolerant varieties.

See page 8.
Photo by David Kuack



COVER STORY

8 Keeping it simple



Jonathan, Georgia and Jerry Soukup of Southwest Perennials like to keep things simple from production techniques to customer service.

FEATURES

- 16 Expand your mix of indoor flowering and foliage plants with the latest introductions from breeders around the world.
- 47 See how plants fared at field trial sites around the country.
- 50 What are the top nine things to incorporate into growing media?
- 54 The fifth in a 6-part series detailing mode-of-action groups for disease control comparing relative efficacy, resistance and phytotoxicity resistance.

Greenhouse Management & Production, formerly **GMPro**, (USPS 013549) is published monthly. Copyright 2010 GIE Media, Inc., 4020 Kinross Lakes Pkwy, Suite 201, Richfield, OH 44286. All rights reserved. No part of this publication may be reproduced or transmitted by any means without permission of the publisher. One-year subscription rates: Free to qualified retailers in the United States. Non-Qualified U.S. subscriptions are \$96 in the United States; \$120 for delivery outside the U.S.; U.S. funds drawn on a U.S. bank required for all foreign subscriptions. Single copy rate: \$8 plus postage while supplies last. Periodicals postage paid at Richfield, Ohio, and additional mailing offices. Postmaster: Send address changes to **Greenhouse Management & Production**, 4020 Kinross Lakes Parkway, Suite 201, Richfield, Ohio 44286. Canada Post: Publications Mail Agreement #40612608. Canada Returns to be sent to Bleuchip International, P.O. Box 25542, London, ON N6C 6B2

